

## **Headset Microphone HS-03**

### **1.APPLICATIONS AND GENERAL APPLICATIONS:**

The HS-03 headset microphone is ideally suited for vocal sound and speech application which requires much freedom of movement.

A built-in windscreen reduces wind and blowing noise and an external windscreen for additional wind noise attenuation is included with the microphone.

High extension cable behind the ear is Inconspicuous.

Miniature gooseneck as the microphone arm can be moved to all directions.

### **2SAFETY NOTES:**

\*Suitable for indoor use only. Protect it against dripping water and splash water, high air humidity, and heat( admissible ambient temperature range 0-40°).

\*For cleanly only use a dry, soft cloth, by no means chemicals water.

\*No guarantee claims for the microphone or liability for any result personal damage or material damage will be accepted if the microphone is used for other purposes than original intend, if it is not correctly connected or not repaired in an expect way.

### **3.HOW TO USE:**

- 1) Put on the microphone and place the microphone cartridge close to the mouth into a favorable talk position. For this purpose this microphone arm can be moved in all the directions.
- 2) Connect the mini XLR inline jack of the microphone cable to the input jack of the pocket transmitter or power supply adaptor, when using a power supply adaptor, connect it to the microphone input of an audio unit.

### **4.SPECIFICATIONS:**

Element:	Back electret condenser
Polar pattern:	Uni-directional
Frequency Response:	50Hz~18KHz
Sensitivity:	-47±3dB
Output impedance:	650Ω
SPL max:	120dB
Power Supply:	1.5-10V D.C.
Cable:	Φ2mm*1.2m
Wight:	42g
Mic.Dimension:	Φ15mm
Output connector:	AKG connector
Accessory:	Windscreen